

**900-1700nm 1mm InGaAs PIN Photodiode****Model:NIP1000****NIP1000-F2****Applications**

- ◆ Optical power meter
- ◆ Optical sensor
- ◆ Science analysis
- ◆ Industrial automatic control
- ◆ Space light detect

**Features**




- ◆ Top illumination Planar PIN PD
- ◆ Low dark current, High reliability
- ◆ Active area diameter 1mm
- ◆ Hermetical TO46 Can

**Absolute Maximum Ratings (Tc=25°C)**

Parameter	Symbol	Unit	value
Storage temperature	Tst	°C	-40 ~ + 100
Operating temperature	Top	°C	-40 ~ + 85
Soldering temperature(time))	Tes ( 10s )	°C	260
Reverse voltage	Vr	V	10

**Optical & electrical characteristics (Tc=25°C)**

Parameter	Symbol	Test Conditions	Unit	value (Typ.)
Response spectrum	λ		nm	900-1700
Active area diameter	Φ		mm	1
Responsivity	Res	Vr=0V,λ=1310nm	mA/mW	0.85
		Vr=0V,λ=1550nm	mA/mW	0.90
Dark current	Id	Vr=0V	nA	0.12
		Vr=5V	nA	1.2
response time	Tre	RL =50Ω,Vr=5V	ns	8
Capacitance	Ct	f=1MHz, Vr=0V	pF	1100
		f=1MHz, Vr=5V	pF	70
Reverse operating voltage	Vr		V	0-5
Reverse breakdown voltage	VBR	Id=10uA	V	30
Saturated optical power	Pso	Vr =5V	mW	15
Shunt resistance	Rsh	Vr =10mV	MΩ	100
Package		Hermetic TO46 Can		

**Dimensions (mm)****Pin Assignment (Bottom View)****NIP1000-F2****Typical responsivity curve( $T_c=25^\circ\text{C}$ )****Order information**

NIP1000-X: N=Ninglight IP=InGaAs PD 1000=1mm active area diameter

X=F2: TO-46 Can with 2mm flat window cap

**The cautions**

- 1: The above product specifications are subject to change without notice.
- 2: The suitable ESD protection is required in storage, transportation and using.